


PLC settings for running PLC attached to roller door model:

Module selection

✕

Select the module category



Select the type of Zelio module to program

Power supply	Discrete Inputs	Mixed Discrete/Analog in	Discrete Outputs	Screen Keyboard	Clock	Language	Reference
24VDC	10 DISCR	6 (0-10V)	10 RELAY	Yes	Yes	FBD/LD	SR3B261BD
24VDC	10 DISCR	6 (0-10V)	10 DISCR STA	Yes	Yes	FBD/LD	SR3B262BD
24VAC	16 DISCR	-	10 RELAY	Yes	Yes	FBD/LD	SR3B261B
100-240VAC	16 DISCR	-	10 RELAY	Yes	Yes	FBD/LD	SR3B261FU
12VDC	10 DISCR	6 (0-10V)	10 RELAY	Yes	Yes	FBD/LD	SR3B261JD


Next > Cancel Help

Module selection

✕

Current selection

Type	SR3B261BD
Power supply	24VDC
Inputs	10 DISCR + 6 (0-10V)
Outputs	10 RELAY
Clock	Yes
Language	FBD/LD



Select extensions

Compatible extensions

Type	Reference	Inputs	Outputs
SR3XT61BD	88960211	4 DISCR	2 RELAY
SR3XT101BD	88960221	6 DISCR	4 RELAY
SR3XT141BD	88960231	8 TOR	6 RELAY
SR3MBU01	88960250	4 INTEGERS	4 INTEGERS
SR3XT43BD	88960241	2 ANALOG 10 BITS	2 ANALOG 10 BITS
SR3NET01	88960270	4 INTEGERS	4 INTEGERS
SR3NET02	88960277	4 INTEGERS	4 INTEGERS

Add Delete

Total number of inputs/outputs

Selected extensions

Type	Reference	Inputs	Outputs
XT2 : SR3XT141BD	88960231	8 TOR	6 RELAY

< Back Next > Cancel Help